

RECOMMENDATIONS

TRANSPORTATION AND STORAGE OF THE FIBER CEMENT BOARDS LATONIT

Every delivery of boards should be accompanied with the document of quality in which the following information about products should be specified:

- logotype (trademark);
- type of product;
- conventional sign of the boards;
- lot number and date of manufacture;
- nominal dimensions;
- test results;
- fire resistance;
- data on sanitary and epidemiological assessment;
- stamp and signature of the authorized person of the Technical Control Service of OAO LATO.

The boards are delivered in transport packages. The packages are formed of boards of the same size, using pallets or supports made of wood, and packed into a polyethylene film.

Transportation of the boards are carried out by any mode of transport in compliance of Regulations Concerning the Carriage of Goods specified for this mode of transport and requirements of other documentation approved in accordance with the established procedure.

When storing and transporting the boards should be protected against damage. It is prohibited to use the damaged boards for facing of facade.

Storage of the boards at the consumer should be carried out in compliance of the following conditions:

- The boards formed in the transport packages can be stored only in horizontal position on the open asphalted or concreted area only if transport package was saved.
- When the transport package was damaged it is necessary to store the board indoor or under cover in the conditions preventing its moistening in order to avoid adfreezing of goods and their damage.
- When the transport packages with boards without decorative coating are stored at the consumer these boards can be set with each other in stacks. In this case total height of stack of the transport packages should not exceed 2.5 m.
- **With the purpose of damage control of the painted surface of the boards while transporting and storing the boards should be interleaved from each other with sealing material — tilit-bazis.**
- It is prohibited to set the transport packages with decorative coating at each other in stacks.
- When opening the package every board should be lifted carefully not to scratch the plate below.
- When loading and unloading, transporting and warehousing and other operations the impacts to the boards and their dropping from any height are not allowed.
- The board should be carried by not less than two persons. When carrying the board it is necessary to hold it in vertical position to prevent breakage.